



APC SMT3000RMI2UC puhvertoiteallikas (UPS) Liini-interaktiivne 3 kVA 2700 W 9 vahelduvvoolu kontakt

Brand : APC  
Product code: SMT3000RMI2UC  
Product name : SMT3000RMI2UC



APC SMT3000RMI2UC. Puhvertoiteallika topoloogia: Liini-interaktiivne, Väljundvõimsuse potentsiaal: 3 kVA, Väljundvõimsus: 2700 W. AC-väljundi tüüp: C13 pistikut, C19 pistikut, Elektripistik: C20 pistikut, AC-väljundite arv: 9 vahelduvvoolu kontakt. Akutehnoloogia: Suletud pliiaku (VRLA), Aku vastupidavus: 547 VAh, Tüübpärane varundamisaeg täiskoormusega: 3,2 min. Toote kuju: Riilule monteeritav, Toote värv: Must, Püstiku mahutavus: 2U. Vastavussertifikaadid: RoHS, Sertifikaat: CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOL



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	3 kVA	Rack capacity	2U
Output power *	2700 W	Cable length	2 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	151 V	Display type	LCD
Input operation voltage (max) *	302 V	LED indicators	Status
Input frequency *	50/60 Hz	Operational conditions	
Output operation voltage (min)	220 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	240 V	Storage temperature (T-T)	-15 - 45 °C
Automatic Voltage Regulation (AVR)	✓	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	320 J	Storage relative humidity (H-H)	0 - 95%
Hold time (min)	4 ms	Operating altitude	0 - 3000 m
Hold time (max)	8 ms	Non-operating altitude	0 - 15000 m
Efficiency	98.9%	Certificates	
Noise level	55 dB	Compliance certificates	RoHS
Audible alarm(s)	✓	Certification	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOL
Auto-restart	✓	Packaging content	
Ports & interfaces		Rack mount kit	✓
AC outlet types	C13 coupler, C19 coupler	Cables included	RS-232, USB cable
Power plug	C20 coupler	Quick installation guide	✓
AC outlets quantity	9 AC outlet(s)	Sustainability	
Number of output IEC jumpers	3	Sustainability certificates	Green Premium
USB port	✓	Weight & dimensions	
Serial interface	✓	Width	432 mm
Serial interface type	RJ-45	Depth	683 mm
Ethernet LAN (RJ-45) ports	1		
SmartSlot	✓		

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Height	86 mm
Battery capacity	547 VAh	Weight	44.3 kg
Typical backup time at full load	3.2 min	Packaging data	
Typical backup time at half load	11.5 min	Software CD	✓
Battery life (max)	5 year(s)	Bundled software	Powershute Business Edition
Battery recharge time	3 h	Package width	600 mm
Hot-swap battery	✓	Package depth	980 mm
Automatic battery test	✓	Package height	254 mm
Cold start	✓	Package weight	51.7 kg
		Logistics data	
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	2968.55
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304337348



731304337348

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-MAR-2025. Prints or copies of Information are only valid on the printed Publication date