



APC SRV1KRIRK puhvertoiteallikas (UPS) Online UPS 1 kVA 800 W
3 vahelduvvoolu kontakt

Brand : APC

Product code: SRV1KRIRK

Product name : SRV1KRIRK




APC SRV1KRIRK. Puhvertoiteallika topoloogia: Online UPS, Väljundvõimsuse potentsiaal: 1 kVA, Väljundvõimsus: 800 W. Elektripistik: C14 pistikut, AC-väljundite arv: 3 vahelduvvoolu kontakt, Jadaliidese tüüp: RS-232. Toote kuju: Riiulile monteeritav, Toote värv: Must, Kuvamise tüüp: LCD. Vastavussertifikaadid: RoHS, Sertifikaat: CE, IEC 62040-1-1, IEC 62040-1-2 REACH. Laius: 437 mm, Sügavus: 312 mm, Kõrgus: 86 mm

Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount
Output power capacity *	1 kVA	Product colour *	Black
Output power *	800 W	Display type	LCD
Waveform *	Sine	LED indicators	✓
Input operation voltage (min) *	160 V	Operational conditions	
Input operation voltage (max) *	280 V	Operating temperature (T-T)	0 - 40 °C
Input frequency *	40/70 Hz	Storage temperature (T-T)	-20 - 50 °C
Output operation voltage (min)	220 V	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (max)	240 V	Storage relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Operating altitude	0 - 9000 m
Surge energy rating	600 J	Non-operating altitude	0 - 14763.6 m
ECO mode	✓	Certificates	
Output voltage Total Harmonic Distortion (THD)	3%	Compliance certificates	RoHS
Audible alarm(s)	✓	Certification	CE, IEC 62040-1-1, IEC 62040-1-2 REACH
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Packaging content	
Ports & interfaces		Rack mount kit	✓
Power plug	C14 coupler	Manual	✓
AC outlets quantity	3 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	437 mm
USB 2.0 ports quantity	1	Depth	312 mm
Serial interface	✓	Height	86 mm
Serial interface type	RS-232	Weight	11 kg
Serial ports quantity	1	Battery width	45.5 cm
SmartSlot	✓	Battery depth	55.1 cm
Battery		Battery height	21.8 cm
Automatic battery test	✓	Battery weight	13.1 kg
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304346166



731304346166



8592978154929

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.