



## DELL Pro Plus P2725DE PC lamekuvar 68,6 cm (27") 2560 x 1440 pikslit Quad HD LCD Must, Hõbe

Brand : DELL

Product family: Pro Plus

Product code: DELL-P2725DE

Product name : P2725DE

DELL Pro Plus P2725DE. Ekraani diagonaal: 68,6 cm (27"), Ekraani resolutsioon: 2560 x 1440 pikslit, HD tüüp: Quad HD, Ekraani tehnoloogia: LCD, Reaktsiooniaeg: 8 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178°, Vaatenurk, vertikaalne: 178°. Sisseehitatud USB-jaotur, USB-jaoturi versioon: 3.2 Gen 1 (3.1 Gen 1). VESA paigaldamine, Kõrguse reguleerimine. Toote värv: Must, Hõbe



Display		Network	
Display diagonal *	68.6 cm (27")	Wi-Fi	✗
Display resolution *	2560 x 1440 pixels	Ethernet LAN	✓
HD type *	Quad HD	<b>Ergonomics</b>	
Native aspect ratio *	16:9	VESA mounting *	✓
Display technology *	LCD	Panel mounting interface	100 x 100 mm
Panel type *	IPS	Wall mountable	✓
LED backlight	✓	Cable management	✓
Backlight type	Edge LED	Cable lock slot *	✓
Touchscreen *	✗	Cable lock slot type	Kensington
Display brightness (typical)	350 cd/m <sup>2</sup>	Height adjustment *	✓
Response time *	8 ms	Adjustable height (max)	15 cm
Response time measurement type	GTG (Gray to Gray)	Pivot	✓
Anti-glare screen	✓	Pivot angle	-90 - 90°
Screen shape *	Flat	Swivelling	✓
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1600 x 900, 1920 x 1080 (HD 1080), 2560 x 1440	Swivel angle range	-45 - 45°
		Tilt adjustment	✓
Supported video modes	480p, 576p, 720p, 1080p	Tilt angle range	-5 - 21°
Contrast ratio (typical) *	1500:1	On Screen Display (OSD)	✓
Maximum refresh rate *	100 Hz	Plug and Play	✓
Viewing angle, horizontal	178°	LED indicators	✓
Viewing angle, vertical	178°	<b>Power</b>	
Display number of colours *	16.7 million colours	Energy efficiency class (SDR) *	E
Response time (fast)	5 ms	Energy efficiency class (HDR) *	Not available
Pixel pitch	0.2331 x 0.2331 mm	Energy consumption (SDR) per 1000 hours *	20 kWh
Pixel density	109 ppi	Power consumption (typical) *	19.6 W
Viewable size, horizontal	59.7 cm	Power consumption (standby) *	0.3 W
Viewable size, vertical	33.6 cm	Power consumption (max)	200 W
Digital horizontal frequency	30 - 151 kHz	Power consumption (off)	0.3 W
Digital vertical frequency	48 - 100 Hz	AC input voltage	100 - 240 V

Display		Power	
High Dynamic Range (HDR) supported	✗	AC input frequency	50/60 Hz
Surface hardness	3H	Power supply type	Internal
sRGB coverage (typical)	99%	Energy efficiency scale	A to G
Performance		Operational conditions	
NVIDIA G-SYNC *	✗	Operating temperature (T-T)	0 - 40 °C
AMD FreeSync *	✗	Storage temperature (T-T)	-20 - 60 °C
Flicker-free technology	✓	Operating relative humidity (H-H)	10 - 80%
Low Blue Light technology	✓	Storage relative humidity (H-H)	5 - 90%
Multimedia		Operating altitude	0 - 5000 m
Built-in speaker(s) *	✗	Non-operating altitude	5000 - 12191 m
Built-in camera *	✗	Weight & dimensions	
Design		Width (with stand)	612.5 mm
Market positioning *	Office	Depth (with stand)	192.2 mm
Product colour *	Black, Silver	Height (with stand)	535.7 mm
Front bezel colour	Black	Weight (with stand)	6.2 kg
Detachable stand	✓	Width (without stand)	612.5 mm
Feet colour	Silver	Depth (without stand)	50 mm
Ports & interfaces		Height (without stand)	356.6 mm
Built-in USB hub *	✓	Weight (without stand)	4.6 kg
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Bezel width (side)	7.88 mm
USB upstream port type	USB Type-C	Bezel width (top)	7.88 mm
Number of USB Type-C upstream ports quantity	1	Bezel width (bottom)	1.3 cm
USB Type-A downstream ports quantity	3	Packaging data	
USB Type-C downstream ports quantity	1	Package weight	8.93 kg
USB Type-C DisplayPort Alternate Mode	✓	Packaging content	
USB Power Delivery (USB PD)	✓	Stand included	✓
USB Power Delivery up to	90 W	Cables included	AC, DisplayPort, USB Type-A to USB Type-C, USB Type-C to USB Type-C
HDMI *	✓	Power adapter included	✗
HDMI ports quantity	1	Remote control included	✗
HDMI version	2.1	Stylus included	✗
DisplayPorts quantity	1	Sustainability	
DisplayPort out quantity	1	Sustainability certificates	ENERGY STAR, TCO
DisplayPort version	1.4	Doesn't contain	Arsenic, Mercury, PVC/BFR
Headphone out *	✗	Other features	
HDCP	✓	RJ-45 ports quantity	1
HDCP version	1.4	Compliance certificates	RoHS



5397184962480

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-MAR-2025. Prints or copies of Information are only valid on the printed Publication date