

## DELL Pro Plus P2725QE PC lamekuvar 68,6 cm (27") 3840 x 2160 pikslit 4K Ultra HD LCD Must, Hõbe

Brand : DELL Product family: Pro Plus Product code: DELL-P2725QE

**Product name :** P2725QE

DELL Pro Plus P2725QE. Ekraani diagonaal: 68,6 cm (27"), Ekraani resolutsioon: 3840 x 2160 pikslit, HD tüüp: 4K Ultra HD, Ekraani tehnoloogia: LCD, Reaktsiooniaeg: 8 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178°, Vaatenurk, vertikaalne: 178°. Sisseehitatud USB-jaotur, USB-jaoturi versioon: 3.2 Gen 1 (3.1 Gen 1). VESA paigaldamine, Kõrguse reguleerimine. Toote värv: Must, Hõbe





Display		Network	
Display diagonal *	68.6 cm (27")	Wi-Fi	×
Display resolution *	3840 x 2160 pixels	Ethernet LAN	/
HD type *	4K Ultra HD	Ergonomics	
Native aspect ratio *	16:9		
Display technology *	LCD	VESA mounting *	<b>/</b>
Panel type *	IPS	Panel mounting interface	100 x 100 mm
LED backlight	✓	Wall mountable	<b>✓</b>
Backlight type	Edge LED	Cable management	✓
Touchscreen *	×	Cable lock slot *	✓
Display brightness (typical)	350 cd/m <sup>2</sup>	Cable lock slot type	Kensington
Response time *	8 ms	Height adjustment *	✓
Response time measurement type	GTG (Gray to Gray)	Adjustable height (max)	15 cm
Anti-glare screen	✓	Pivot	<b>✓</b>
Screen shape *	Flat	Pivot angle	-90 - 90°
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1600 x 900, 1920 x 1080 (HD 1080), 2560 x 1440, 3840 x 2160	Swivelling	<b>✓</b>
		Swivel angle range	-45 - 45°
		Tilt adjustment	<b>✓</b>
		Tilt angle range	-5 - 21°
Supported video modes	480p, 576p, 720p, 1080p, 2160p	On Screen Display (OSD)	<b>✓</b>
Contrast ratio (typical) *	1500:1	Plug and Play	<b>✓</b>
Maximum refresh rate *	100 Hz	LED indicators	<b>✓</b>
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°		-
Display number of colours *	16.7 million colours	Energy efficiency class (SDR) *	F. Maria attacks
Response time (fast)	5 ms	Energy efficiency class (HDR) *	Not available
Pixel pitch	0.1554 x 0.1554 mm	Energy consumption (SDR) per 1000 hours *	26 kWh
Pixel density	163 ppi	Power consumption (typical) *	19.6 W
Viewable size, horizontal	59.7 cm	Power consumption (standby) *	0.3 W
Viewable size, vertical	33.6 cm	Power consumption (max)	200 W
Digital horizontal frequency	30 - 227 kHz	Power consumption (off)	0.3 W
Digital vertical frequency	48 - 100 Hz	AC input voltage	100 - 240 V

Display		Power	
High Dynamic Range (HDR) supported Surface hardness	X 3H	AC input frequency Power supply type Energy efficiency scale	50/60 Hz Internal A to G
sRGB coverage (typical)	99%	Operational conditions	
Performance  NVIDIA G-SYNC *  AMD FreeSync *  Flicker-free technology  Low Blue Light technology	× × •	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12191 m
Multimedia		Weight & dimensions	
Built-in speaker(s) * Built-in camera *	×	Width (with stand) Depth (with stand)	612.5 mm 192.2 mm
Design  Market positioning *  Product colour *  Front bezel colour  Detachable stand  Feet colour	Office Black, Silver Black ✓ Silver	Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) Weight (without stand) Bezel width (side)	535.7 mm 6.23 kg 612.5 mm 50 mm 356.6 mm 4.62 kg 7.88 mm
Ports & interfaces		Bezel width (side)  Bezel width (top)	7.88 mm
Built-in USB hub *	✓	Bezel width (bottom)	1.3 cm
USB hub version USB upstream port type Number of USB Type-C upstream	3.2 Gen 1 (3.1 Gen 1) USB Type-C 1	Packaging data Package weight	9.02 kg
ports quantity	1	Packaging content	
USB Type-A downstream ports quantity	3	Stand included	✓
USB Type-C downstream ports quantity	1	Cables included	AC, DisplayPort, USB Type-A to USB Type-C, USB Type-C to USB Type-C
USB Type-C DisplayPort Alternate Mode	/	Power adapter included Remote control included	×
USB Power Delivery (USB PD)	✓	Stylus included	×
USB Power Delivery up to	90 W	Sustainability	
HDMI * HDMI ports quantity HDMI version	1 2.1	Sustainability certificates Doesn't contain	ENERGY STAR, TCO Arsenic, Mercury, PVC/BFR
DisplayPorts quantity	1	Other features	
DisplayPort version	1.4	RJ-45 ports quantity	1
Headphone out *	×	Compliance certificates	RoHS
HDCP	✓		
HDCP version	2.3		



5397184962497

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.