be quiet! Pure Base 501 DX White Midi Tower Valge

Brand : be quiet! **Product code:** BGW77

Product name: Pure Base 501 DX White

be quiet! Pure Base 501 DX White. Toote kuju: Midi Tower, Tüüp: PC, Toote värv: Valge. Toetatud elektritoite tarne vormi faktorid: ATX, PS2. Installitud esiventilaatorid: 1x 140 mm, Toetatud esiventilaatorite läbimõõt: 120,140 mm, Installitud tagaventilaatorid: 1x 140 mm. Toetatud kõvakettasuurused: 2.5,3.5". Laius: 231 mm, Sügavus: 450 mm, Kõrgus: 463 mm





Design Cooling Material (ABS), Glass, Steel (ABS), Glass, Steel (ABS), Glass, Steel (Top fans installed (MaX)) 120,140 mm Form factor * Midi Tower Number of top fans supported (MaX) 2 Product colour * White Top fans diameters supported (MaX) 2 Supported motherboard form factors * ATX, micro ATX, Mini-ATX Maximum airflow (Max) 57.4 cfm Number of 3.5" bays * 2 Fan rated voltage (ST) (ST) (ST) (ST) (ST) (ST) (ST) (ST)				
Midi Tower Number of top fans installed 1x 140 mm 1x 140	Design		Cooling	
Form factor * Midi Tower Number of top fans supported (max) Number of top fans supported (max) 2 Type * PC (max) 2 Product colour * White Top fans diameters supported 120,140 mm Supported motherboard form factors * ATX, micro ATX, Mini-ATX Maximum airflow 57.4 cfm Number of 3.5" bays * 2 Fan rated voltage 5-13.2 V Number of 2.5" bays 5 Fan rated voltage 5-13.2 V Number of expansion slots 7 Fan power consumption 3.6 W Side window * Maximum air pressure 0.96 mmH2O Illumination * Liquid cooling capability 2,040,240,280,360 mm Illumination colour Multi Rear radiator sizes supported 120,140,240,280,360 mm Illumination location Front Rear radiator sizes supported 120,140 mm Anti-dust filter * Top radiator sizes supported 120,140 mm Maximum graphics card length 36.8 cm Supported HDD sizes supported 25,3.5" Power supply Included * X Supp	Material		Rear fans diameters supported	120,140 mm
Type * PC Minited (max) (max) PC Product colour * White Top fans diameters supported 120,140 mm Supported motherboard form factors * ATX, micro ATX, Mini-ATX (mois level (high speed) 21.9 dB Number of 3.5" bays * 2 Fan rated voltage 5 - 13.2 V Number of 2.5" bays 5 Fan rated current 0.06 A Number of expansion slots 7 Fan power consumption 3.6 W Side window ✓ Maximum air pressure 0.96 mmH2O Illumination colour Multi Front radiator sizes supported 120,140,240,280,360 mm Illumination location Front Rear radiator sizes supported 120,140,240,280,360 mm Anti-dust filter ✓ Top radiator sizes supported 120,140,240,280,360 mm Maximum graphics card length 36.8 cm Pulse-width modulation (PWM) ✓ Maximum PSU length 2 cm Supported HDD sizes * 2.5,3.5" Power supply included * X Supported HDD sizes * 2.5,3.5" Ports & interfaces ATX, PS2 Supported HDD sizes * 2.			Top fans installed	1x 140 mm
Type PC			·	2
Supported motherboard form factors * noise level (high speed) 57.4 cfm factors factors * noise level (high speed) 21.9 dB Number of 3.5" bays * 2 Number of 2.5" bays 5 Fan rated voltage 5 - 13.2 V Number of 2.5" bays 5 Fan rated voltage 5 - 13.2 V Number of expansion slots 7 Fan power consumption 3.6 W Side window ✓ Maximum air pressure 0.96 mmH2O Illumination ✓ Liquid cooling capability ✓ Illumination location Front Rear radiator sizes supported 120,140,240,280,360 mm Illumination location Front Rear radiator sizes supported 120,140,40,240,280,360 mm Illumination location Front Rear radiator sizes supported 120,140,400,240,280,360 mm Illumination location Front Rear radiator sizes supported 120,140 mm Maximum graphics card length 36.8 cm supported 120,240 mm Maximum pSU length X Storage Supported power supply form factors ATX, PS2 Supported HDD sizes * 2.5,3.5" Audio input ✓ Co	* *		, ,	
factors * AIX, MINCR AIX, MINIFAIX Noise level (high speed) 21.9 dB Number of 3.5" bays * 2 Fan rated voltage 5 - 13.2 V Number of 2.5" bays 5 Fan rated current 0.06 A Number of expansion slots 7 Fan power consumption 3.6 W Side window * Maximum air pressure 0.96 mmH2O Illumination * Liquid cooling capability * Illumination loctour Multi Front radiator sizes supported 120,140,240,280,360 mm Illumination location Front Rear radiator sizes supported 120,140 mm Anti-dust filter * Top radiator sizes supported 120,140 mm Maximum graphics card length 36.8 cm Pulse-width modulation (PWM) * Maximum PSU length 20 cm Supported 2.5,3.5" Power supply Fower supply included * X Supported HDD sizes * 2.5,3.5" Supported HDD sizes * 2.5,3.5" Supported power supply form factors * * *		White		• •
Number of 3.5" bays 2 Fan rated voltage 5 - 13.2 V Number of 2.5" bays 5 Fan rated current 0.06 A Number of expansion slots 7 Fan power consumption 3.6 W Side window V Maximum air pressure 0.96 mmH2O Illumination V Liquid cooling capability V Illumination colour Multi Front radiator sizes supported 120,140,240,280,360 mm Illumination location Front Rear radiator sizes supported 120,140 mm Anti-dust filter V Top radiator sizes supported 120,240 mm Maximum graphics card length 36.8 cm Pulse-width modulation (PWM) V Maximum PSU length 20 cm Storage 2.5,3.5" Power supply X Supported HDD sizes * 2.5,3.5" Supported power supply form factors ATX, PS2 Fachical details Triman Ports & interfaces X Sustainability certificates Triman Audio input V Weight & dimensions USB 3.2 Gen 2 (3.1 Gen 2) Type-C 2	• •	ATX, micro ATX, Mini-ATX		
Number of 2.5" bays 5 7 Fan rated current 3.6 W Number of expansion slots 7 Fan power consumption 3.6 W Side window 4 Maximum air pressure 0.96 mmH2O 11 Mination 10 V 12 Milumination 10 V 12 Milumin	Number of 3.5" bays *	2	, , ,	
Number of expansion slots Side window V Maximum air pressure 0.96 mmH2O Illumination V Illumination Multi Front radiator sizes supported 120,140,240,280,360 mm Illumination location Illumination location Anti-dust filter V Maximum graphics card length Maximum graphics card length Maximum PSU length V Power supply Power supply included * Supported power supply form factors ATX, PS2 Supported power supply form factors ATX, PS2 Warranty period Warranty perio	Number of 2.5" bays	5	•	
Side windowYMaximum air pressure0.96 mmH2OIlluminationYLiquid cooling capabilityYIllumination colourMultiFront radiator sizes supported120,140,240,280,360 mmIllumination locationFrontRear radiator sizes supported120,140 mmAnti-dust filterYTop radiator sizes supported120,240 mmMaximum graphics card length36.8 cmPulse-width modulation (PWM) supportYMaximum PSU length20 cmStoragePower supplyStorage2.5,3.5"Power supply included *XSupported HDD sizes *2.5,3.5"Supported power supply form factorsATX, PS2Sustainability certificatesTrimanPorts & interfacesWarranty period3 year(s)Audio inputYCompliance certificatesCE, RoHS, UKCA, WEEEAudio outputYWeight & dimensionsUSB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *YWidth Depth231 mmUSB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *2Height Weight463 mmUSB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *2Height Weight7,9 kgCoolingFront fans installed1x 140 mmPackage width292 mmNumber of front fans supported3Package height503 mmFront fans diameters supported120,140 mmPackage height503 mm	Number of expansion slots	7		
Illumination V Liquid cooling capability V Illumination colour Multi Front radiator sizes supported 120,140,240,280,360 mm Illumination location Front Rear radiator sizes supported 120,140 mm Anti-dust filter V Top radiator sizes supported 120,240 mm Maximum graphics card length 36.8 cm Pulse-width modulation (PWM) support V Maximum PSU length 20 cm Storage Power supply X Supported HDD sizes * 2.5,3.5" Supported power supply form factors XX Technical details Supported power supply form factors XX Sustainability certificates Triman Ports & interfaces X Compliance certificates Triman Audio input Y Compliance certificates CE, RoHS, UKCA, WEEE Audio output Y Width 231 mm USB 3.2 Gen 2 (3.1 Gen 2) Type-C 1 Depth 450 mm USB 3.2 Gen 2 (3.1 Gen 2) Type-C 2 Height 463 mm ports quantity * Y Weight 463 mm USB 3.2 Gen 2 (3.1 Gen 2) Type-C Package width 92 mm Front fans installed 1x 140 mm Package depth 518 mm	Side window	✓	·	
Illumination colour Multi Front radiator sizes supported 120,140,240,280,360 mm Illumination location Front Rear radiator sizes supported 120,140 mm 120,240	Illumination	1	•	
Illumination location Front Rear radiator sizes supported 120,140 mm Anti-dust filter ✓ Top radiator sizes supported 120,240 mm Maximum graphics card length 36.8 cm Pulse-width modulation (PWM) support ✓ Power supply Included X Supported HDD sizes 2.5,3.5" Power supply included X Supported HDD sizes 2.5,3.5" Supported power supply form factors ATX, PS2 Technical details Sustainability certificates Triman Ports & interfaces Warranty period 3 year(s) Audio input ✓ Compliance certificates CE, RoHS, UKCA, WEEE Audio output ✓ Weight & dimensions USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity 2 Dopth Height 463 mm Dopth 463 mm Dopth 463 mm Dotted fans installed 1x 140 mm Number of front fans supported 3 Front fans diameters supported 120,140 mm Package height 518 mm Front fans diameters supported 120,140 mm Package height 50.01 mm Double to the product of the package height Colon means the pack		Multi		
Anti-dust filter			• •	
Maximum graphics card length Maximum PSU length 36.8 cm 20 cm Pulse-width modulation (PWM) support Verification (PWM) support (Post in part (PW)) support Verification (PWM) support (PW) suppor			• •	•
Maximum PSU length20 cmsupportStoragePower supply included *XSupported HDD sizes *2.5,3.5"Supported power supply form factorsATX, PS2Technical detailsPorts & interfacesWarranty period3 year(s)Audio input✓Compliance certificatesCE, ROHS, UKCA, WEEEAudio output✓Weight & dimensionsUSB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *1Width Depth450 mmUSB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *2Height Weight463 mmUSB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *2Packaging dataFront fans installed1x 140 mmPackage width292 mmNumber of front fans supported (max)3Package depth518 mmFront fans diameters supported120,140 mmPackage depth518 mm		•		120,240 111111
Power supply Power supply included * X Supported HDD sizes * 2.5,3.5" Supported power supply form factors ATX, PS2 ATX, PS2 AUdio input Audio input Audio output Au	5 .		` ,	✓
Power supply included * X Supported power supply form factors ATX, PS2 Technical details Sustainability certificates Triman Ports & interfaces Audio input Audio output Weight & dimensions USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * Cooling Front fans installed Number of front fans supported (max) Front fans diameters supported 120,140 mm Supported HDD sizes * 2.5,3.5" Technical details Sustainability certificates Triman A year(s) Compliance certificates CE, RoHS, UKCA, WEEE Weight & dimensions Width Depth 450 mm 450 mm Weight 7.9 kg Packaging data Package width Package width Package width Package depth S18 mm Package height Package height Package height Package width Package width Package width Package height Package width Package width Package height Package width Package width Package height Package height Package width Package width Package width Package width Package width Package height Package width Package width Package width Package width Package height Package width Package wi	-		Storage	
Supported power supply form factors ATX, PS2 Rorts & interfaces Audio input Audio output Weight & dimensions USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * Cooling Front fans installed Number of front fans supported (max) Front fans diameters supported ATX, PS2 Triman Triman Audio output Weight & dimensions Width Depth Depth 450 mm 463 mm Weight Packaging data Front fans diameters supported Package depth Package depth Package height 503 mm Package height Package height Package width Package height Package width Package height Package height Package width Package height Package width Package height Package height	Power supply included *	*	Supported HDD sizes *	2.5,3.5"
Factors ATX, PS2 Sustainability certificates Triman Warranty period 3 year(s) Compliance certificates CE, RoHS, UKCA, WEEE Audio output Weight & dimensions USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * Cooling Cooling Front fans installed 1x 140 mm Number of front fans supported (max) Front fans diameters supported 120,140 mm Sustainability certificates Triman Warranty period 3 year(s) Ce, RoHS, UKCA, WEEE Width 231 mm 450 mm Height Weight Height Weight Packaging data Package width Package width Package width Package depth Foot fans diameters supported (max) Package height Package height Package height Package height Package height Package width Package height Package height Package height Package height Package height Package height			Technical details	
Ports & interfacesWarranty period3 year(s)Audio input✓Compliance certificatesCE, RoHS, UKCA, WEEEAudio output✓Weight & dimensionsUSB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *1Width Depth231 mmUSB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *2Height Weight463 mmCoolingHeight Weight7.9 kgFront fans installed1x 140 mmPackaging dataNumber of front fans supported (max)1x 140 mmPackage width292 mmFront fans diameters supported120,140 mmPackage height503 mm		ATX, PS2		Trimon
Audio input Audio output V Weight & dimensions USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * Cooling Front fans installed Number of front fans supported (max) Front fans diameters supported 120,140 mm Neight Cooling CE, RoHS, UKCA, WEEE Weight 231 mm Depth 450 mm Height Weight 7.9 kg Packaging data Package width 292 mm Package depth 518 mm Package height 503 mm Package height 503 mm	Parts & interfaces		•	
Audio output Veight & dimensions USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * Cooling Front fans installed Number of front fans supported (max) Front fans diameters supported 1 Veight & dimensions Width 231 mm Depth 450 mm Weight 463 mm Weight 7.9 kg Packaging data Package width 292 mm Package depth 518 mm Package height 503 mm Package height 503 mm			7 '	• • • •
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * Cooling Front fans installed Number of front fans supported (max) Front fans diameters supported 1	•	1		CL, ROITS, ORCA, WELL
ports quantity * Depth 450 mm USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * Packaging data Front fans installed 1x 140 mm Number of front fans supported (max) Front fans diameters supported 120,140 mm Depth 450 mm Weight 7.9 kg Packaging data Package width 292 mm Package depth 518 mm Package height 503 mm	Audio output	✓	Weight & dimensions	
ports quantity * Depth 450 mm USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * Height 463 mm Weight 7.9 kg Cooling Front fans installed 1x 140 mm Number of front fans supported (max) 3 Package depth 518 mm Front fans diameters supported 120,140 mm Package width 9ackage height 503 mm Package weight 503 mm		1	Width	231 mm
ports quantity * Veight 7.9 kg Cooling Front fans installed 1x 140 mm Number of front fans supported (max) Front fans diameters supported 120,140 mm Package width 292 mm Package depth 518 mm Package height 503 mm		-	Depth	450 mm
Cooling Front fans installed Number of front fans supported (max) Front fans diameters supported 120,140 mm Weight 7.9 kg Packaging data Package width Package width Package depth Package depth Package height So3 mm Package height		2	Height	463 mm
Front fans installed 1x 140 mm Package width 292 mm Number of front fans supported (max) Package depth 518 mm Front fans diameters supported 120,140 mm Package height 503 mm			Weight	7.9 kg
Front fans installed Number of front fans supported (max) Front fans diameters supported 1x 140 mm Package width Package depth Package depth Package height	9		Packaging data	
Number of front fans supported (max) Package depth Package height 518 mm Package height 503 mm		1x 140 mm	Package width	292 mm
Front fans diameters supported 120,140 mm Package height 503 mm	• • • • • • • • • • • • • • • • • • • •	3	3	
Poster and submitted 120,140 mm	,	120 140		
Rear fans installed 1x 140 mm 1 decays weight 9.2 kg	• • • • • • • • • • • • • • • • • • • •	• •		
	Rear fans installed	1x 140 mm	r dendge Weight	3.2 Kg

Cooling	Other features		
Number of rear fans supported	Volume	24.4 L	
(max)	Fan connector	4-pin	



4260052192849

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.