tp-link

TP-Link TAPO C530WS turvakaamera Torn IP süsteemiga turvakaamera Hooneväline 2880 x 1620 pikslit Sein

Brand : TP-Link

Product name : TAPO C530WS

Product code: TAPO C530WS

TP-Link TAPO C530WS. Tüüp: IP süsteemiga turvakaamera, Toetatud paigutus: Hooneväline, Ühenduvustehnoloogia: Juhtmega ühendatud & juhtmevaba. Kinnituse tüüp: Sein, Toote värv: Valge, Toote kuju: Torn. Objektiivi vaatenurk, horisontaalne: 95°, Objektiivi vaatenurk, vertikaalne: 53°, Objektiivi vaatenurk, diagonaalne: 112°. Anduri tüüp: CMOS, Optilise sensori suurus: 25,4 / 3 mm (1 / 3"). Sensori tüüp (panoraamkaamera): CMOS

Performance		Audio	
Type *	IP security camera	Audio formats supported	RTSP
Placement supported *	Outdoor	Built-in microphone	✔
Connectivity technology *	Wired & Wireless	Number of microphones	1
Auto pan mode	✔	Audio detection	✔
Maximum operating distance	29.9 m	**Network**	
Day/night mode	✔	Ethernet LAN *	✔
Remote viewing	✔	Networking standards	IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Antenna type	External		
Antennas quantity	2	Wi-Fi *	✔
Design		Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Form factor *	Turret	Bluetooth *	✘
Mounting type *	Wall	Live view	✔
Product colour *	White	**Storage**	
Housing material	Metal	Compatible memory cards	MicroSD (TransFlash)
Protection features	Waterproof	Maximum memory card size	512 GB
International Protection (IP) code	IP66	**Ports & interfaces**	
Weatherproof	✔	Ethernet LAN (RJ-45) ports	1
Camera		**Security**	
Camera pan control	✔	Built-in siren	✔
Camera tilt control	✔	Siren noise level	99 dB
Lens viewing angle, horizontal	95°	Video motion detection	✔
Lens viewing angle, vertical	53°	HTTPS encryption	✔
Lens viewing angle, diagonal	112°	Alert notification type	Push notification
Tilt angle range	60 - 130°		

Image sensor

Optical sensor size	25.4 / 3 mm (1 / 3")
Progressive scan	✔
Sensor type *	CMOS

Panoramic camera

Sensor type (panoramic camera)	CMOS

Lens system

Digital zoom	12x
Focal length range	3.2 mm

Night vision

Night vision *	✔
LED type	IR/White

Video

Maximum resolution *	2880 x 1620 pixels
Total megapixels *	5 MP
Video compression formats	H.264
Supported graphics resolutions	2880 x 1620
Video recording	✔
Frame rate	30 fps
Image quality adjustment	DNR

Audio

Built-in speaker(s)	✔
Audio system	2-way
Audio input channels	1 channels
Audio output channels	1 channels

Security

Motion sensor	✔
Mirror	✔

Management features

Cloud-managed *	✔
Reset button	✔
Remotely operated	✔

Power

Power source type *	AC, DC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
DC output voltage	9
DC output current	0.85 A

Operational conditions

Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	0 - 90%

Weight & dimensions

Width	123.8 mm
Depth	90 mm
Height	123 mm

Packaging data

Package type	Box

Packaging content

Number of cameras *	1
Mounting kit	✔
Mounting brackets included	✔
Screws included	✔
Drilling template included	✔
Manual	✔

1210002606745

8885020624984

8885020629200