

TP-Link Omada EAP673-Extender Võrguvõimendi Valge 10, 100, 1000 Mbit/s

Brand : TP-Link **Product family:** Omada **Product code:** EAP673-EXTENDER

Product name: EAP673-

Extender


TP-Link Omada EAP673-Extender. Tüüp: Võrguvõimendi, Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s. Antenni tüüp: Väline, Saatja võimsus (CE): <20 dBm (2.4 GHz, EIRP) <23 dBm (5 GHz, band1 & band2, EIRP) <30 dBm (5 GHz, band3, EIRP), Saatja võimsus (FCC): <25 dBm (2.4 GHz) <28 dBm (5 GHz). Võrgustandardid: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, WiFi-standardid: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), WiFi andmeedastuskiirus (maksimaalne): 4800 Mbit/s. Toote värv: Valge, Korpuse materjal: Polükarbonaat, Kogus pakis: 1 tk. AC-sisendpinge: 100 - 240 V, AC-sisendsagedus: 50/60 Hz, Elektritarbimine (max): 18 W





Performance		Management features	
Type *	Network repeater	Airtime scheduling	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Power	
BeamForming	✓	AC input voltage	100 - 240 V
Antenna		AC input frequency	50/60 Hz
Antennas quantity	4	Power consumption (max)	18 W
Antenna type	External	Operational conditions	
Transmitting power (CE)	<20 dBm (2.4 GHz, EIRP) <23 dBm (5 GHz, band1 & band2, EIRP) <30 dBm (5 GHz, band3, EIRP)	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -40 - 70 °C
Transmitting power (FCC)	<25 dBm (2.4 GHz) <28 dBm (5 GHz)	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 90% 5 - 90%
Network		Weight & dimensions	
Networking standards Wi-Fi	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n ✓	Width Depth Height Weight	80 mm 37.8 mm 160 mm 436.6 q
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Packaging content	.55.0 g
Wi-Fi data rate (max)	4800 Mbit/s	Quick start guide	✓
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)	Certificates	
Security algorithms	64-bit WEP, 128-bit WEP, WPA-PSK, WPA2-PSK	Compliance certificates	CE, Federal Communications Commission (FCC), JRF, RCM, RoHS,
Ports & interfaces			UL, VCCI
Ethernet LAN (RJ-45) ports	1		
Design			
Product colour Housing material Quantity per pack	White Polycarbonate (PC) 1 pc(s)		

Design	
Reset button	✓



8885020622874

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.