



iiyama LH6541UHS-B1AG infoekraan 163,8 cm (64.5") LCD 500 cd/m² 4K Ultra HD Must 24/7

Brand : iiyama

Product code: LH6541UHS-B1AG

Product name : LH6541UHS-B1AG

iiyama LH6541UHS-B1AG. Ekraani diagonaal: 163,8 cm (64.5"), Ekraani tehnoloogia: LCD, Ekraani resolutsioon: 3840 x 2160 pikslit, Ekraani heledus: 500 cd/m², HD tüüp: 4K Ultra HD. Töötunnid (tunnid/päevad): 24/7. Toote värv: Must



Display		Design	
Panel type	VA	Panel mounting interface	500 x 500 mm
Display diagonal *	163.8 cm (64.5")	Performance	
Display technology *	LCD	Purpose *	Universal
Display resolution *	3840 x 2160 pixels	On Screen Display (OSD)	✓
Display brightness *	500 cd/m²	On Screen Display (OSD) languages	German, Dutch, English, Spanish, French, Italian, Japanese, Russian
HD type *	4K Ultra HD	Operating hours (hours/days)	24/7
Touchscreen *	✗	HDCP	✓
Native aspect ratio	16:9	HDCP version	2.2
Response time	6.5 ms	Mean time between failures (MTBF)	50000 h
Contrast ratio (typical)	5000:1	Power	
Viewing angle, horizontal	178°	Power consumption (typical) *	115 W
Viewing angle, vertical	178°	Power consumption (standby) *	0.5 W
Display number of colours	1.07 billion colours	Power consumption (off)	0.3 W
Pixel pitch	0.372 x 0.372 mm	Energy efficiency class (SDR)	G
Active display area (W x H)	1428.5 x 803.5 mm	Energy consumption (SDR) per 1000 hours	115 kWh
Display diagonal (metric)	164 cm	AC input voltage	100-240 V
Colour saturation	72%	AC input frequency	50/60 Hz
Horizontal scan range	30 - 80 kHz	Energy efficiency scale	A to G
Ports & interfaces		Weight & dimensions	
HDMI ports quantity *	3	Display width	1456.5 mm
HDMI version	2.0	Display depth	69 mm
USB port *	✓	Display height	831.5 mm
USB version	2.0	Display weight	17.7 kg
Ethernet LAN *	✓	Packaging data	
Ethernet LAN (RJ-45) ports	1	Package width	1640 mm
RS-232C	✓	Package depth	164 mm
Remote (IR) input	1	Package height	990 mm
Audio			
Built-in speaker(s) *	✓		

Audio		Packaging data	
Number of built-in speakers	2	Package weight	25.7 kg
RMS rated power	10 W	Operational conditions	
Design		Operating temperature (T-T)	0 - 40 °C
Orientation	Horizontal/Vertical	Storage temperature (T-T)	-20 - 60 °C
Product colour *	Black		
VESA mounting *	✓		



4948570124558

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-MAY-2025. Prints or copies of Information are only valid on the printed Publication date