

DELL Tower Plus EBT2250 Intel Core Ultra 7 32 GB DDR5-SDRAM 2 TB SSD NVIDIA GeForce RTX 4070 Windows 11 Pro PC Grafiit

Brand : DELL Product family: Tower Plus Product code: EBT2250_ARL_007

Product name: EBT2250

DELL Tower Plus EBT2250. Protsessori perekond: Intel Core Ultra 7. Sisemälu: 32 GB, Sisemälu tüüp: DDR5-SDRAM. Salvestusmaht kokku: 2 TB, Salvestusseade: SSD, Integreeritud kaardilugeja. Pardagraafika adapteri mudel: Intel Graphics, Eraldiseisva graafika adapteri mudel: NVIDIA GeForce RTX 4070. Installitud operatsioonisüsteem: Windows 11 Pro, Operatsioonisüsteemi arhitektuur: 64-bit. Toiteallikas: 750 W. Keretüüp: Tower. Toote tüüp: PC. Kaal: 12,9 kg. Toote värv: Grafiit





Processor		Network	
Processor manufacturer * Processor family * Processor generation Processor cores Processor threads	Intel Intel Core Ultra 7 Intel Core Ultra (Series 2) 12 14	Wi-Fi standards WLAN controller manufacturer WLAN controller model	802.11a, Wi-Fi 5 (802.11ac), Wi-Fi 7 (802.11be), 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6E (802.11ax) Intel Intel Wi-Fi 7 BE200
Processor boost frequency	5.3 GHz	Bluetooth	✓
Performance cores	2	Ports & interfaces	
Efficient cores	8	USB 2.0 ports quantity *	4
Low Power Efficient-cores	2	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	5
Performance-core Max Turbo Frequency	5.3 GHz	ports quantity * USB 3.2 Gen 2 (3.1 Gen 2) Type-C	1
Efficient-core Max Turbo Frequency	4.2 GHz	ports quantity *	1
Low Power Efficient-core Max Turbo Frequency	2.4 GHz	PowerShare	✓
Performance-core base frequency	2.1 GHz	Number of USB ports with PowerShare support	2
Efficient-core base frequency	1.7 GHz	USB Type-C DisplayPort Alternate	✓
Low Power Efficient-core Base Frequency	700 MHz	Mode	
Processor cache	12 MB	Intel® Thunderbolt 4	·
Number of processors installed	1	Thunderbolt 4 ports quantity	1
Processor base power	15 W	HDMI ports quantity * HDMI version	1 2.0
Maximum turbo power	57 W	Ethernet LAN (RJ-45) ports	2.0
·		Line-out	
Neural processor unit (NPU)			✓
Neural processor unit (NPU)	Intel Al Boost	Line-in	✓

Neural processor unit (NPU)		Ports & interfaces	
Sparsity support	✓	Combo headphone/mic port	✓
Windows Studio effects support	✓	S/PDIF out port	✓
Al software frameworks supported	DirectML, ONNX RT, OpenVINO,	Total number of SATA connectors	3
by NPU	Windows ML	Expansion slots	
Memory		PCI Express x4 (Gen 3.x) slots	2
Internal memory *	32 GB	PCI Express x16 (Gen 5.x) slots	1
Maximum internal memory *	64 GB	Design	
Internal memory type	DDR5-SDRAM	Chassis type *	Tower
Memory layout (slots x size)	1 x 32 GB	Volume	27.1 L
Memory slots	2x DIMM	Placement supported	Vertical
Memory channels Memory data transfer rate	Single-channel 5200 MT/s	Number of 3.5" bays	2
•	3200 H1/3	Cable lock slot	✓
Storage		Cable lock slot type	Kensington
Total storage capacity *	2 TB	Product colour *	Graphite
Storage media *	SSD	Performance	
Optical drive type *	X 1	Motherboard chipset	Intel Z890
Number of storage drives installed Total SSDs capacity	2 TB	Audio chip	Realtek ALC1220
Number of SSDs installed	1	Audio system	High Definition Audio
SSD capacity	2 TB	Audio output channels	7.1 channels
SSD interface	PCI Express	Password protection	✓
NVMe	/	Trusted Platform Module (TPM)	✓
SSD form factor	M.2	Trusted Platform Module (TPM)	2.0
Card reader integrated	✓	version	
Compatible memory cards	SD, SDHC, SDXC	Product type *	PC
Graphics		Software	
Discrete graphics card *	✓	Operating system installed *	Windows 11 Pro
Discrete GPU manufacturer	NVIDIA	Operating system architecture	64-bit
On-board graphics card * Discrete graphics card model * Discrete graphics card memory	NVIDIA ✓	Trial software	McAfee Premium 1Yr, Microsoft Office Trial
	NVIDIA GeForce RTX 4070	Power	
	12 GB	Power supply *	750 W
Discrete graphics memory type	GDDR6X	Power supply input voltage	90 - 264 V
Number of discrete graphics cards	1	Power supply input frequency	47 - 63 Hz
On-board GPU manufacturer	Intel Craphics	80 PLUS certification	80 PLUS Platinum
On-board graphics card family On-board graphics card model *	Intel Graphics Intel Graphics	Operational conditions	
Graphics card HDMI ports quantity	1	Operating temperature (T-T)	10 - 35 °C
Graphics card DisplayPorts quantity	3	Storage temperature (T-T)	-40 - 65 °C
Network		Operating relative humidity (H-H)	20 - 80%
Ethernet LAN *	✓	Storage relative humidity (H-H)	5 - 95%
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Operating altitude	-15.2 - 3048 m
Wi-Fi *	10,100,1000,2300 Mbit/S	Non-operating altitude	-15.2 - 10668 m
Top Wi-Fi standard	Wi-Fi 7 (802.11be)	Operating vibration	0.26 G
Top Wi-i i Standard	WI-117 (002.11De)	Non-operating vibration	1.37 G 40 G
		Operating shock Non-operating shock	105 G
			103 0
		Weight & dimensions	172
		Width *	173 mm
		Depth *	426.9 mm 372.9 mm
		Height *	314.3 111111
		Weight *	12.9 kg
		Weight * Display	12.9 kg
			12.9 kg

