

DELL Tower Plus EBT2250 Intel Core Ultra 7 32 GB DDR5-SDRAM 1 TB SSD NVIDIA GeForce RTX 4060 Ti Windows 11 Pro PC Grafiit

Brand : DELL Product family: Tower Plus Product code: EBT2250_ARL_004

Product name: EBT2250

DELL Tower Plus EBT2250. Protsessori perekond: Intel Core Ultra 7. Sisemälu: 32 GB, Sisemälu tüüp: DDR5-SDRAM. Salvestusmaht kokku: 1 TB, Salvestusseade: SSD, Integreeritud kaardilugeja. Pardagraafika adapteri mudel: Intel Graphics, Eraldiseisva graafika adapteri mudel: NVIDIA GeForce RTX 4060 Ti. Installitud operatsioonisüsteem: Windows 11 Pro, Operatsioonisüsteemi arhitektuur: 64-bit. Toiteallikas: 750 W. Keretüüp: Tower. Toote tüüp: PC. Kaal: 12,9 kg. Toote värv: Grafiit





Processor		Network	
Processor manufacturer * Processor family * Processor generation Processor cores	Intel Intel Core Ultra 7 Intel Core Ultra (Series 2) 12	Wi-Fi standards WLAN controller manufacturer	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6E (802.11ax), Wi-Fi 7 (802.11be) Intel
Processor threads Processor boost frequency	14 5.3 GHz	WLAN controller model Bluetooth	Intel Wi-Fi 7 BE200 ✓
Performance cores	2	Ports & interfaces	
Efficient cores	8	USB 2.0 ports quantity *	4
Low Power Efficient-cores	2	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	5
Performance-core Max Turbo Frequency	5.3 GHz	ports quantity * USB 3.2 Gen 2 (3.1 Gen 2) Type-C	1
Efficient-core Max Turbo Frequency	4.2 GHz	ports quantity *	1
Low Power Efficient-core Max Turbo Frequency	2.4 GHz	PowerShare	✓
Performance-core base frequency	2.1 GHz	Number of USB ports with PowerShare support	2
Efficient-core base frequency	1.7 GHz	USB Type-C DisplayPort Alternate Mode	✓
Low Power Efficient-core Base Frequency	700 MHz	Intel® Thunderbolt 4	✓
Processor cache	12 MB	Thunderbolt 4 ports quantity	1
Number of processors installed	1	HDMI ports quantity *	1
Processor base power	15 W	HDMI version	2.0
Maximum turbo power	57 W	Ethernet LAN (RJ-45) ports	1
Neural processor unit (NPU)		Line-out	✓
Neural processor unit (NPU)	Intel Al Boost	Line-in	✓

Neural graceses unit (NDII)		Danta C intenferes	
Neural processor unit (NPU)		Ports & interfaces	
Sparsity support	✓	Combo headphone/mic port	✓
Windows Studio effects support	V	S/PDIF out port	✓
Al software frameworks supported by NPU	DirectML, ONNX RT, OpenVINO, Windows ML	Total number of SATA connectors	3
		Expansion slots	
Memory	22.60	PCI Express x4 (Gen 3.x) slots	2
Internal memory * Maximum internal memory *	32 GB 64 GB	PCI Express x16 (Gen 5.x) slots	1
Internal memory type	DDR5-SDRAM	Design	
Memory layout (slots x size)	1 x 32 GB	Chassis type *	Tower
Memory slots	2x DIMM	Volume	27.1 L
Memory channels	Single-channel	Placement supported	Vertical
Memory data transfer rate	5200 MT/s	Number of 3.5" bays	2
Storage		Cable lock slot	Vancington
Total storage capacity *	1 TB	Cable lock slot type Product colour *	Kensington Graphite
Storage media *	SSD		Grapinice
Optical drive type *	x	Performance	latal 7000
Number of storage drives installed	1	Motherboard chipset Audio chip	Intel Z890 Realtek ALC1220
Total SSDs capacity	1 TB	Audio cnip Audio system	High Definition Audio
Number of SSDs installed	1 1 TB	Audio output channels	7.1 channels
SSD capacity SSD interface	PCI Express	Password protection	✓
NVMe	✓	Trusted Platform Module (TPM)	✓
SSD form factor	M.2	Trusted Platform Module (TPM)	2.0
Card reader integrated	✓	version	
Compatible memory cards	SD, SDHC, SDXC	Product type *	PC
Graphics		Software	
Discrete graphics card *	✓	Operating system installed *	Windows 11 Pro
Discrete GPU manufacturer	NVIDIA	Operating system architecture	64-bit
On-board graphics card *	✓	Trial software	McAfee Premium 1Yr, Microsoft Office Trial
Discrete graphics card model *	NVIDIA GeForce RTX 4060 Ti	Power	
Discrete graphics card memory	8 GB	Power supply *	750 W
Discrete graphics memory type	GDDR6	Power supply input voltage	90 - 264 V
Number of discrete graphics cards On-board GPU manufacturer	1 Intel	Power supply input frequency	47 - 63 Hz
On-board graphics card family	Intel Graphics	80 PLUS certification	80 PLUS Platinum
On-board graphics card model *	Intel Graphics	Operational conditions	
Graphics card HDMI ports quantity	1	Operating temperature (T-T)	10 - 35 °C
Graphics card DisplayPorts quantity	3	Storage temperature (T-T)	-40 - 65 °C
Network		Operating relative humidity (H-H)	20 - 80%
Ethernet LAN *	✓	Storage relative humidity (H-H)	5 - 95%
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Operating altitude Non-operating altitude	-15.2 - 3048 m -15.2 - 10668 m
Wi-Fi *	✓	Operating vibration	0.26 G
Top Wi-Fi standard			
	Wi-Fi 7 (802.11be)		1.37 G
	Wi-Fi 7 (802.11be)	Non-operating vibration Operating shock	1.37 G 40 G
	Wi-Fi 7 (802.11be)	Non-operating vibration	
	Wi-Fi 7 (802.11be)	Non-operating vibration Operating shock	40 G
	Wi-Fi 7 (802.11be)	Non-operating vibration Operating shock Non-operating shock	40 G
	Wi-Fi 7 (802.11be)	Non-operating vibration Operating shock Non-operating shock Weight & dimensions	40 G 105 G
	Wi-Fi 7 (802.11be)	Non-operating vibration Operating shock Non-operating shock Weight & dimensions Width * Depth * Height *	40 G 105 G 173 mm 426.9 mm 372.9 mm
	Wi-Fi 7 (802.11be)	Non-operating vibration Operating shock Non-operating shock Weight & dimensions Width * Depth *	40 G 105 G 173 mm 426.9 mm
	Wi-Fi 7 (802.11be)	Non-operating vibration Operating shock Non-operating shock Weight & dimensions Width * Depth * Height *	40 G 105 G 173 mm 426.9 mm 372.9 mm
	Wi-Fi 7 (802.11be)	Non-operating vibration Operating shock Non-operating shock Weight & dimensions Width * Depth * Height * Weight *	40 G 105 G 173 mm 426.9 mm 372.9 mm

