



DELL Pro Plus P3225DE PC lamekuvar 80 cm (31.5") 2560 x 1440 pikslit Wide Quad HD LCD Must, Hall

Brand : DELL

Product family: Pro Plus

Product code: DELL-P3225DE

Product name : P3225DE

DELL Pro Plus P3225DE. Ekraani diagonaal: 80 cm (31.5"), Ekraani resolutsioon: 2560 x 1440 pikslit, HD tüüp: Wide Quad HD, Ekraani tehnoloogia: LCD, Reaktsiooniaeg: 8 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178°, Vaatenurk, vertikaalne: 178°. Sisseehitatud USB-jaotur. VESA paigaldamine, Kõrguse reguleerimine. Toote värv: Must, Hall



Display		Ergonomics	
Display diagonal *	80 cm (31.5")	VESA mounting *	✓
Display resolution *	2560 x 1440 pixels	Panel mounting interface	100 x 100 mm
HD type *	Wide Quad HD	Cable management	✓
Native aspect ratio *	16:9	Cable lock slot *	✓
Display technology *	LCD	Cable lock slot type	Kensington
Panel type *	IPS	Height adjustment *	✓
LED backlight	✓	Adjustable height (max)	15 cm
Backlight type	Edge LED	Pivot	✓
Touchscreen *	✗	Pivot angle	-90 - 90°
Display brightness (typical)	350 cd/m ²	Swivelling	✓
Response time *	8 ms	Swivel angle range	-30 - 30°
Response time measurement type	GTG (Gray to Gray)	Tilt adjustment	✓
Anti-glare screen	✓	Tilt angle range	-5 - 21°
Screen shape *	Flat	On Screen Display (OSD)	✓
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1600 x 1200, 1920 x 1080 (HD 1080), 2560 x 1440	Plug and Play	✓
Supported video modes	480p, 576p, 720p, 1080p	LED indicators	✓
Contrast ratio (typical) *	1500:1	Power	
Maximum refresh rate *	100 Hz	Energy efficiency class (SDR) *	E
Viewing angle, horizontal	178°	Energy efficiency class (HDR) *	Not available
Viewing angle, vertical	178°	Energy consumption (SDR) per 1000 hours *	23 kWh
Display number of colours *	1.07 billion colours	Power consumption (typical) *	23.1 W
Response time (fast)	5 ms	Power consumption (standby) *	0.4 W
Pixel pitch	0.2727 x 0.2727 mm	Power consumption (max)	192 W
Pixel density	93 ppi	Power consumption (off)	0.3 W
Horizontal scan range	30 - 151 kHz	AC input voltage	100 - 240 V
Vertical scan range	48 - 100 Hz	AC input frequency	50/60 Hz
Viewable size, horizontal	69.8 cm	Input current	2.8 A
Viewable size, vertical	39.3 cm	Power supply type	Internal
Viewable size diagonal	80.1 cm	Energy efficiency scale	A to G

Display		Operational conditions	
Surface hardness	3H	Operating temperature (T-T)	0 - 40 °C
sRGB coverage (typical)	99%	Storage temperature (T-T)	-20 - 60 °C
Dell ComfortView technology	✓	Operating relative humidity (H-H)	10 - 80%
Heat dissipation (typical)	78.8 BTU/h	Storage relative humidity (H-H)	5 - 90%
Performance		Operating altitude	0 - 5000 m
NVIDIA G-SYNC *	✗	Non-operating altitude	0 - 12192 m
AMD FreeSync *	✗	Weight & dimensions	
Flicker-free technology	✓	Width (with stand)	713.4 mm
Low Blue Light technology	✓	Depth (with stand)	215 mm
Windows operating systems supported	Windows 10	Height (with stand)	619 mm
Mac operating systems supported	✓	Weight (with stand)	9.14 kg
Multimedia		Width (without stand)	713.4 mm
Built-in speaker(s) *	✗	Depth (without stand)	50 mm
Built-in camera *	✗	Height (without stand)	413.1 mm
Design		Weight (without stand)	6.63 kg
Product colour *	Black, Grey	Bezel width (side)	7.64 mm
Front bezel colour	Black	Bezel width (top)	7.45 mm
Feet colour	Grey	Bezel width (bottom)	1.3 cm
Ports & interfaces		Packaging data	
Built-in USB hub *	✓	Package weight	12.9 kg
Number of USB Type-C upstream ports quantity	1	Packaging content	
USB Type-A downstream ports quantity	3	Stand included	✓
USB Type-C downstream ports quantity	1	Cables included	DisplayPort, USB Type-A to USB Type-C, USB Type-C
USB Type-C DisplayPort Alternate Mode	✓	DisplayPort cable length	1.8 m
USB Power Delivery (USB PD)	✓	Sustainability	
USB Power Delivery up to	90 W	Sustainability certificates	ENERGY STAR, EPEAT Climate +, EPEAT Gold, TCO
HDMI *	✓	Doesn't contain	Arsenic, Mercury, PVC/BFR
HDMI ports quantity	1	Other features	
DisplayPorts quantity	2	Compliance certificates	RoHS
DisplayPort version	1.4	Ethernet LAN data rates	1000 Mbit/s
Headphone out *	✗	Ethernet LAN (RJ-45) ports	1
HDCP	✓	Wake-on-LAN	✓
HDCP version	1.4	Certification	TÜV Rheinland Eye Comfort 3.0
		Brand-specific features	
		Dell Display Manager (DDM) compatibility	✓



5397184962503

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-MAY-2025. Prints or copies of Information are only valid on the printed Publication date