DELL

DELL Pro Plus P2725D PC lamekuvar 68,6 cm (27") 2560 x 1440 pikslit Quad HD LCD Must, Hõbe

Brand : DELL   **Product family:** Pro Plus   **Product code:** DELL-P2725D

Product name : P2725D

DELL Pro Plus P2725D. Ekraani diagonaal: 68,6 cm (27"), Ekraani resolutsioon: 2560 x 1440 pikslit, HD tüüp: Quad HD, Ekraani tehnoloogia: LCD, Reaktsiooniaeg: 8 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178°, Vaatenurk, vertikaalne: 178°. Sisseehitatud USB-jaotur, USB-jaoturi versioon: 3.2 Gen 1 (3.1 Gen 1). VESA paigaldamine, Kõrguse reguleerimine. Toote värv: Must, Hõbe

Display

Display diagonal *	68.6 cm (27")
Display resolution *	2560 x 1440 pixels
HD type *	Quad HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	IPS
LED backlight	✔
Backlight type	Edge LED
Touchscreen *	✘
Display brightness (typical)	350 cd/m²
Response time *	8 ms
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	✔
Screen shape *	Flat
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1600 x 900, 1920 x 1080 (HD 1080), 2560 x 1440
Supported video modes	480p, 576p, 720p, 1080p
Contrast ratio (typical) *	1500:1
Maximum refresh rate *	100 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Response time (fast)	5 ms
Pixel pitch	0.2331 x 0.2331 mm
Pixel density	109 ppi
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Digital horizontal frequency	30 - 151 kHz
Digital vertical frequency	48 - 100 Hz

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Wall mountable	✔
Cable management	✔
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Adjustable height (max)	15 cm
Pivot	✔
Pivot angle	-90 - 90°
Swivelling	✔
Swivel angle range	-45 - 45°
Tilt adjustment	✔
Tilt angle range	-5 - 21°
On Screen Display (OSD)	✔
Plug and Play	✔
LED indicators	✔

Power

Energy efficiency class (SDR) *	E
Energy efficiency class (HDR) *	Not available
Energy consumption (SDR) per 1000 hours *	19 kWh
Power consumption (typical) *	18.8 W
Power consumption (standby) *	0.3 W
Power consumption (max)	75 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Display

High Dynamic Range (HDR) supported	✘
Surface hardness	3H
sRGB coverage (typical)	99%

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
Flicker-free technology	✔
Low Blue Light technology	✔

Multimedia

Built-in speaker(s) *	✘
Built-in camera *	✘

Design

Market positioning *	Office
Product colour *	Black, Silver
Front bezel colour	Black
Detachable stand	✔
Feet colour	Silver

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B
Number of USB Type-B upstream ports quantity	1
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
HDMI *	✔
HDMI ports quantity	1
HDMI version	2.1
DisplayPorts quantity	1
DisplayPort version	1.4
Headphone out *	✘
HDCP	✔
HDCP version	1.4

Network

Wi-Fi	✘

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	5000 - 12191 m

Weight & dimensions

Width (with stand)	612.5 mm
Depth (with stand)	192.2 mm
Height (with stand)	535.7 mm
Weight (with stand)	5.88 kg
Width (without stand)	612.5 mm
Depth (without stand)	50 mm
Height (without stand)	356.6 mm
Weight (without stand)	4.28 kg
Bezel width (side)	7.88 mm
Bezel width (top)	7.88 mm
Bezel width (bottom)	1.3 cm

Packaging data

Package weight	8.67 kg

Packaging content

Stand included	✔
Cables included	AC, DisplayPort, USB Type-A to USB Type-B
Power adapter included	✘
Remote control included	✘
Stylus included	✘
DisplayPort cable length	1.8 m

Sustainability

Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	Arsenic, Mercury, PVC/BFR

Other features

Compliance certificates	RoHS

5397184962473