



MSI MPG A1000G PCIE5 toiteallika komponent 1000 W 20+4 pin ATX ATX Must

Brand : MSI

Product family: MPG

Product code: MPG A1000G PCIE5

Product name : A1000G PCIE5



MSI MPG A1000G PCIE5. Koguvõimsus: 1000 W, AC-sisendpinge: 100 - 240 V, AC-sisendsagedus: 50 - 60 Hz. Emaplaadi toitepistik: 20+4 pin ATX, Emaplaadi toitekaabli pikkus: 60 cm, SATA toitekaabli pikkus: 500,650,700,850 mm. Otstarve: PC/server, Toiteploki (PSU) standard: ATX, 80 PLUS sertifikaat: 80 PLUS Gold. Toote värv: Must, Jahutuse tüüp: Aktiivne, Ventilaatori läbimõõt: 13,5 cm. Laius: 150 mm, Sügavus: 150 mm, Kõrgus: 86 mm

Võimsus		Pesad & liidesed	
Koguvõimsus *	1000 W	Välisseadmete (Molex) toitepistikud (4 kontakti) *	4
AC-sisendpinge *	100 - 240 V	Välise (Molex) toitekaabli pikkus	1100,500,650,700,850 mm
AC-sisendsagedus	50 - 60 Hz	EPS-toitepistik (8 kontakti)	✗
Võimsusteguri korrigeerimise (PFC) tüüp	Aktiivne	EPS toitepistik (4+4 pinn)	✓
Kombineeritud võimsus (+3,3 V)	120 W	PCI Expressi toitepistikud (6 + 2 kontakti)	6
Kombineeritud võimsus (+12 V)	1000 W	PCI Expressi toitepistikud (16 kontaktiga)	1
Kombineeritud võimsus (+5 V)	120 W	PCI Express toitekaabli pikkus	75 cm
Kombineeritud võimsus (-12 V)	3,6 W	Flopidraivi pistmik	✓
Kombineeritud võimsus (+5 Vsb)	15 W	Kaabelduse tüüp	Täielikult modulaarne
Maksimaalne väljundvool (+3,3 V)	22 A	Toimimine	
Maksimaalne väljundvool (+12 V)	83,5 A	80 PLUS sertifikaat *	80 PLUS Gold
Maksimaalne väljundvool (+5 V)	22 A	Otstarve *	PC/server
Maksimaalne väljundvool (-12 V)	0,3 A	Toiteploki (PSU) standard *	ATX
Maksimaalne väljundvool (+5 Vsb)	3 A	ATX-versioon	3.0
Tõhusus	90 protsenti	Laagertehnoloogia	FDB
Toite kaitsefunktsioonid	Ülevool, Ülevõimsus, Ülepinge, Ülekütmine, Lühis, Alapinge	Disain	
Pesad & liidesed		Toote värv	Must
Emaplaadi toitepistik *	20+4 pin ATX	Jahutuse tüüp	Aktiivne
Emaplaadi toitekaabli pikkus	60 cm	Ventilaatori läbimõõt	13,5 cm
SATA-toitepistmike arv	12	Ventilaatorite arv	1 ventilaator(id)
SATA toitekaabli pikkus	500,650,700,850 mm	Valgustus	✗
		Kaal ja mõõtmed	
		Laius	150 mm
		Sügavus	150 mm
		Kõrgus	86 mm
		Muud funktsioonid	
		EPS kaabli pikkus	70 cm



4719072972196

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.