

TP-Link IES206GPP võrgulüliti Juhitav Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Must

Brand : TP-Link

Product code: IES206GPP

Product name : IES206GPP

TP-Link IES206GPP. Lüliti tüüp: Juhitav. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 4. MAC-aadresside tabel: 8000 sisestust, Lülitusvõime: 12 Gbit/s. Võrgustandardid: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE.... Alalisvoolu sisendpinge: 12 - 57 V. Power over Ethernet tugi. Seinale kinnitav, Püstikmontaaž



Juhtimisfunktsioonid		Disain	
Lüliti tüüp *	Juhitav	Seinale kinnitav	✓
Pesad & liidesed		DIN-liistu paigaldamine	✓
RJ-45 Etherneti ühenduse pesade arv *	4	Toimimine	
RJ-45 Etherneti ühenduse pesade tüüp *	Gigabit Ethernet (10/100/1000)	Ilma ventilaatorita	✓
Kombineeritud SFP-pesade arv	1	Võimsus	
SFP mooduli pesade arv	1	Toiteallikas *	DC/PoE
Võrgustumine		Üleliigse toite (RPS) tugi	✓
Võrgustandardid *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3x	Alalisvoolu sisendpinge	12 - 57 V
10G-tugi *	✗	Internet elektrivõrgu kaudu (PoE)	
Pordipeegeldus	✓	Power over Ethernet tugi *	✓
Voo reguleerimise tugi	✓	Toide üle võrgu (PoE) toetatud tüüp	PoE+, PoE++ (4PPoE)
Linkide koondamine	✓	Toide üle võrgu (PoE) pesade arv	3
Levindamise torni kontroll	✓	Etherneti toitega 4PPoE (PoE++) portide kogus	1
Auto MDI/MDI-X	✓	Toide üle võrgu (PoE) võimsus pordi kohta	30 W
Genereeriva puu protokoll	✓	Toide üle võrgu (PoE) võimsusühikuid kokku	120 W
Ethernet LAN-i andmeedastuskiirused	10,100,1000 Mbit/s	Töötingimused	
Automaatne ühildumine	✓	Kasutamistemperatuur (T-T)	-40 - 75 °C
		Hoiustamistemperatuur (T-T)	-40 - 85 °C

Andmeedastus		Töötingimused	
Lülitusvõime *	12 Gbit/s	Suhteline õhuniiskus kasutamisel (H-H)	5 - 95 protsenti
Edastamise kiirus	8,93 Mpps	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 95 protsenti
MAC-aadresside tabel *	8000 sisestust	Kaal ja mõõtmed	
Ladusta-ja-edasta	✓	Laius	155 mm
Hiielkaadrite tugi	✓	Sügavus	120 mm
Hiielkaadrite	15000	Kõrgus	60 mm
Turvalisus		Pakendi sisu	
DHCP elemendid	DHCP client	Kiirstardi juhend	✓
IGMP-jälgimine	✓	Sertifikaadid	
Multisaate tunnused		Sertifikaat	FCC, CE, RoHS
Multiedastuse tugi	✓		
Disain			
Püstikmontaaž *	✓		
Toote värv	Must		



1210002602051



0840460600927



840460600927

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.