



Dahua Technology CS4009-8ET1GT-60 võrgulüliti Juhitav L2 Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Lauaarvuti/seinale paigaldamine Sinine

Brand : Dahua Technology

Product code: CS4009-8ET1GT-60

Product name : CS4009-8ET1GT-60

Dahua Technology CS4009-8ET1GT-60. Lüliti tüüp: Juhitav, Lüliti kiht: L2. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 9. MAC-aadresside tabel: 8000 sisestust, Lülitusvõime: 3,6 Gbit/s. Võrgustandardid: IEEE 802.3af, IEEE 802.3at, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3az, IEEE.... Alalisvoolu sisendpinge: 53 V. Toitepistik: Alaldi sisendi pesa. Power over Ethernet tugi. Toote kuju: Lauaarvuti/seinale paigaldamine

Juhtimisfunktsioonid		Disain	
Lüliti tüüp *	Juhitav	Toote kuju	Lauaarvuti/seinale paigaldamine
Lüliti kiht	L2	Toote värv	Sinine
Veebipõhine haldus	✓	Korpuse materjal	Metall
Pilvepõhine haldus	✓	LED-indikaatorid	✓
Süsteemisündmuste logi	✓	Toimimine	
Pesad & liidesed		Keskmine tõrkeintervall (MTBF)	3253425 h
RJ-45 Etherneti ühenduse pesade arv *	9	Võimsus	
RJ-45 Etherneti ühenduse pesade tüüp *	Gigabit Ethernet (10/100/1000)	Toiteallikas *	DC/PoE
Kiire Etherneti (vask) pesade arv	8	Kaasas toiteplokk *	✓
Gigabitise Etherneti (vask) portide arv	1	Alalisvoolu sisendpinge	53 V
Toitepistik	Alaldi sisendi pesa	Sisendvool	1.22 A
Võrgustumine		Elektritarbimine (max)	63 W
Võrgustandardid *		Internet elektrivõrgu kaudu (PoE)	
10G-tugi *	✗	Power over Ethernet tugi *	✓
Pordipeegeldus	✓	Töötingimused	
Voo reguleerimise tugi	✓	Kasutamistemperatuur (T-T)	-10 - 55 °C
Levindamise tormi kontroll	✓	Hoiustamistemperatuur (T-T)	-40 - 70 °C
VLAN-i tugi	✓	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
VLAN-ide arv	32	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 95 protsenti
Andmeedastus		Kaal ja mõõtmed	
Lülitusvõime *	3,6 Gbit/s	Laius	103,3 mm
Edastamise kiirus	2,68 Mpps	Sügavus	184,6 mm
MAC-aadresside tabel *	8000 sisestust	Kõrgus	27 mm
Hiielkaadrite tugi	✓	Pakendi sisu	
Hiielkaadrite arv	9216	Kaablid kaasa arvatud	Vahelduvvool
Paketi puhvermälu	4 MB	Juhend	✓
Turvalisus		Pakendi andmed	
DHCP elemendid	DHCP client	Pakendi laius	137 mm
Tsükli kaitse	✓	Pakendi sügavus	252 mm
IP-MAC pordi sidumine	✓	Pakendi kõrgus	113 mm
Disain		Pakendi kaal	920 g
Püstikmontaaž *	✗	Sertifikaadid	
		Vastavussertifikaadid	CE

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.