



## DELL PowerEdge T560 server 8 TB Torn (4.5U) Intel® Xeon® Silver 4510 2,4 GHz 32 GB DDR5-SDRAM 1100 W

Brand : DELL

Product family: PowerEdge

Product code:  
EMEA\_PROMO\_T560\_SPL2

Product name : T560

DELL PowerEdge T560. Protsessori perekond: Intel® Xeon® Silver, Protsessori sagedus: 2,4 GHz, Protsessori mudel: 4510. Sisemälu: 32 GB, Sisemälu tüüp: DDR5-SDRAM. Salvestusmaht kokku: 8 TB, Kõvaketta suurus: 3.5", Kõvaketta liides: Liides SCSI (SAS). Ethernet LAN, Kaabeldustehnoloogia: 10/100/1000Base-T(X). Toiteallikas: 1100 W, Üleliigse toite (RPS) tugi. Keretüüp: Torn (4.5U)



| Protsessor                               |                     | Pesad & liidesed                                            |                                                                                                                                                        |
|------------------------------------------|---------------------|-------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protsessori tootja *                     | Intel               | Ethernet LAN (RJ-45) pordid *                               | 2                                                                                                                                                      |
| Protsessori perekond *                   | Intel® Xeon® Silver | USB 2.0 portide arv                                         | 2                                                                                                                                                      |
| Protsessori mudel *                      | 4510                | USB 3.2 Gen 1 (3.1 Gen 1) A-tüüpi portide hulk              | 2                                                                                                                                                      |
| Protsessori sagedus *                    | 2,4 GHz             | VGA (D-Sub) portide arv                                     | 1                                                                                                                                                      |
| Protsessori võimendussagedus             | 4,1 GHz             | <b>Disain</b>                                               |                                                                                                                                                        |
| Protsessorituumad                        | 12                  | Keretüüp *                                                  | Torn (4.5U)                                                                                                                                            |
| Protsessori vahemälu                     | 30 MB               | Toote värv                                                  | Hall                                                                                                                                                   |
| Emaplaadi kiip                           | Intel C741          | <b>Tarkvara</b>                                             |                                                                                                                                                        |
| Installeeritud protsessorite arv         | 1                   | Installitud operatsioonisüsteem *                           | ✗                                                                                                                                                      |
| Jahutusvõimsus (TDP)                     | 150 W               | Ühilduvad operatsioonisüsteemid *                           | Canonical® Ubuntu® Server LTS<br>Microsoft® Windows Server® with Hyper-V<br>RedHat® Enterprise Linux<br>SUSE® Linux Enterprise Server<br>VMware® ESXi® |
| Süsteemi siinikiirus                     | 16 GT/s             | <b>Võimsus</b>                                              |                                                                                                                                                        |
| Protsessori harud                        | 24                  | Üleliigse toite (RPS) tugi *                                | ✓                                                                                                                                                      |
| Protsessori poolt toetatud mälu tüübid   | DDR5-SDRAM          | Toiteallikas *                                              | 1100 W                                                                                                                                                 |
| Protsessori poolt toetatud mälu kiirused | 4400 MHz            | Installeeritud lisatoite allikate arv                       | 2                                                                                                                                                      |
| Mälu                                     |                     | <b>Sertifikaadid</b>                                        |                                                                                                                                                        |
| Sisemälu *                               | 32 GB               | 80 PLUS sertifikaat                                         | 80 PLUS Titanium                                                                                                                                       |
| Sisemälu tüüp *                          | DDR5-SDRAM          | <b>Süsiniku jalajälg</b>                                    |                                                                                                                                                        |
| Mälupesad                                | 16x DIMM            | Süsinikujalajälg kokku (kg of CO2e)                         | 5989                                                                                                                                                   |
| Maksimaalne sisemälu *                   | 1 TB                | Süsinikdioksiidi heitkogused kokku, standardhälve (kg CO2e) | 3189                                                                                                                                                   |
| Salvesti                                 |                     | Süsinikdioksiidi heitkogused, tootmine (kg CO2e)            | 419,23                                                                                                                                                 |
| Salvestusmaht kokku *                    | 8 TB                |                                                             |                                                                                                                                                        |
| Installitud kõvaketaste arv              | 2                   |                                                             |                                                                                                                                                        |
| Kõvakettamaht                            | 4 TB                |                                                             |                                                                                                                                                        |
| Kõvaketta liides                         | Liides SCSI (SAS)   |                                                             |                                                                                                                                                        |
| Kõvaketta kiirus                         | 7200 RPM            |                                                             |                                                                                                                                                        |
| Kõvaketta suurus                         | 3.5"                |                                                             |                                                                                                                                                        |
| Toetatud kõvaketaste arv                 | 8                   |                                                             |                                                                                                                                                        |

| Salvesti                   |                            | Süsiniku jalajälg                                              |                  |
|----------------------------|----------------------------|----------------------------------------------------------------|------------------|
| Toetatud kõvakettasuurus   | 3.5"                       | Süsinikdioksiidi heitkogused, logistika (kg CO2e)              | 299,45           |
| RAID-tugi *                | ✓                          | Süsinikdioksiidi heitkogused, energiakasutus (kg CO2e)         | 5210,43          |
| Toetatud RAID-kontrollerid | Front PERC H755 Front Load | Süsinikdioksiidi heitkogused, kasutuselt kõrvaldatud (kg CO2e) | 59,89            |
| Hot-Plug tugi              | ✓                          | PAIA versioon                                                  | PAIA 1.3.2, 2022 |
| Optilise seadme tüüp *     | ✗                          | Kaal ja mõõtmed                                                |                  |
| Võrgustumine               |                            | Laius                                                          | 200 mm           |
| Ethernet LAN               | ✓                          | Muud funktsioonid                                              |                  |
| Kaabeldustehnoloogia       | 10/100/1000Base-T(X)       | Andmeedastuskiirus                                             | 12 Gbit/s        |
| Ethernet-liidese tüüp      | Gigabit Ethernet           | Baiti sektori kohta                                            | 512n             |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.