Canon

Canon i-SENSYS MF3010 Laser A4 1200 x 600 DPI 18 lk/min

Brand : Canon Product family: i-SENSYS Product code: 5252B004

Product name: MF3010

Canon i-SENSYS MF3010. Printimistehnoloogia: Laser, Printimine: Mono printimine, Maksimaalne resolutsioon: 1200×600 DPI. Kopeerimine: Mono kopeerimine, Maksimaalne kopeerimisresolutsioon: 600×600 DPI. Skaneerimine: Värviskaneerimine, Optilise skaneerimise resolutsioon: 600×600 DPI. Maksimaalne ISO A-seeria paberi suurus: A4. Toote värv: Must





Printing		Paper handling	
Print technology * Printing * Duplex printing * Maximum resolution * Print speed (black, normal quality,	Laser Mono printing X 1200 x 600 DPI quality, 10 pages	Non-ISO print media sizes Envelopes sizes Custom media width Custom media length Paper tray media weight	Executive, Statement B5, C5, Com-10, DL 76 - 216 mm 127 - 356 mm 60 - 163 g/m ²
A4/US Letter) * Warm-up time Time to first page (black, normal) Print margins (top, bottom, right, left)	18 ppm 10 s 7.8 s 5 mm	Ports & interfaces Standard interfaces USB port USB 2.0 ports quantity	USB 2.0 ✓ 1
Economical printing	✓	Network	
Copying		Wi-Fi *	×
Duplex copying * Copying *	X Mono copying	Ethernet LAN * Performance	×
Maximum copy resolution * Copy speed (black, normal quality, A4) Time to first copy (black, normal) Maximum number of copies	600 x 600 DPI 18 cpm 12 s 9 copies	Card reader integrated Internal memory * Sound pressure level (printing) Sound power level (standby)	X 64 MB 65.3 dB 43 dB
Copier resize N-in-1 copy function (N=)	50 - 200% 2	Design Product colour *	Black
Scanning		Market positioning *	Home & office
Duplex scanning * Scanning * Optical scanning resolution * Maximum scan resolution	Colour scanning 600 x 600 DPI 9600 x 9600 DPI	Power Power consumption (max) Power consumption (average operating)	960 W 450 W
Maximum scan area Scanner type *	A4 / Letter (216 x 297) Flatbed scanner	Power consumption (PowerSave) Power consumption (standby)	450 W 1.4 W

Scanning		Power	
Input colour depth Output colour depth Greyscale levels Scan drivers	24 bit 24 bit 256 TWAIN, WIA	Energy Star Typical Electricity Consumption (TEC) AC input voltage AC input frequency	0.6 kWh/week 220 - 240 V 50 - 60 Hz
Fax	TWAIN, WIA	System requirements	
Duplex faxing Faxing *	x x		Windows 2000, Windows 2000 Professional, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows
Features			7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home
Maximum duty cycle * Number of print cartridges * Printing colours * Page description languages	8000 pages per month 1 Black UFRII-LT		Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows Vista
Input & output capacity		Business, Windows Vista Business	
Total input capacity * Total output capacity *	150 sheets 100 sheets	Windows Vista Home Basic,	Windows Vista Enterprise x64, Windows Vista Home Basic,
Paper handling			Windows Vista Home Basic x64, Windows Vista Home Premium,
Maximum ISO A-series paper size * Maximum print size Paper tray media types *	A4 216 x 356 mm Card stock, Coated paper, Envelopes, Labels, Plain paper, Recycled paper, Transparencies		Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9)	A4, A5 B5	Mac operating systems supported	Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion
		Linux operating systems supported	✓
		Windows operating systems supported d paper, Plain paper, ransparencies Mac operating systems supported Linux operating systems supported Operational conditions Operating relative humidity (H-H) Operating temperature (T-T) Sustainability Sustainability certificates Weight & dimensions Width Depth Height Height Weight	
		, -	20 - 80% 10 - 30 °C
		Sustainability	
		Sustainability certificates	ENERGY STAR
		Weight & dimensions	
		Depth Height	372 mm 276 mm 254 mm 8.2 kg
		Logistics data	
		Harmonized System (HS) code	84433100



4960999783574

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.